

CIRCUIT TECHNICAL BULLETIN no. 3/2011

PORSCHE CUP 996									
SLICK		OLD IP CODE	NEW IP CODE	possible MIX	TYRE SIZE	RIM WIDTH	P. TARGET (bar)	P. MIN (bar)	CAMBER MAX
	FRONT	2015400	2015400		245/645-18 SLICK DM	9	2	1,45	4,2°
	REAR	2006800	2128100	NO	315/675-18 SLICK DH*	11	2.05	1,5	4,5°
WET									
	FRONT	1796900	1796900		245/645-18 RAIN WS ***	9	2,2	1,7	4,0°
	REAR	1798600	1798600		305/680-18 RAIN WS ***	11	2,2	1,7	4,5°

P. TARGET

is the optimum pressure value for the tyre. The pressure should be measured immediately after the use of the tyre on the track. NEVER set the pressure at lower values than suggested.

P. MIN

is the minimum pressure value. NEVER use the tyre below the minimum pressure otherwise you will compromise the integrity of the tyre. The minimum pressure needs to be checked before the car is moved

Pressure below the minimum value will cause excessive deflection of the sidewall and risk of air loss, compromising the integrity of the tyre.

During the first lap out from the pit and the warm up lap we strongly recommend to avoid impacts with rumble strips and curbs to prevent any tyre pressure loss

P. COLD:

is the pressure that is measured before mounting the tyre on the car, or before the use of tyre warmers, or before the start of any track session

This value need to be determined with respect to the P. MIN value so you can achieve the P TARGET during the use of the tyre on the

This value need to be checked and adjusted to the calculated value at the same time every day until the end of the event.

P. RATN

pressure for the rain tyre changes according to the depth of standing water on the track. The cold pressure should not be less than 1.55 bar when the track is damp.

CAMBER (negative) MAX:

is the maximum negative camber permitted. Negative camber greater than this value can compromise the integrity of the tyre.

- * Same dimension from 2010 spec Ip code 2006800 short code 68X, different dimension from 2009 305/680-18 Ip code 1798700 short code 90V
- *** Will be a new tyres coming after meddle of the season, please let me know the stock you have avaible from this spec 2010

Pirelli strongly recommends the use of metal valves.